

Our exclusive Optiview indoor speed dome camera allows you to pan, tilt, or zoom up to 220X. With a crystal clear image day or night and a full OSD allowing access to all functions - it can't be beat at this price!

Note: To use a PTZ camera on our PC-Based DVRs, you must have an RS485 Converter.

Product Includes

- Power supply
- Installation / Instruction Manual
- Free technical support

Features

- 22X Optical Zoom
- 10X Digital Zoom
- On Screen Display menu
- 127 Presets
- Patterns: 8 patterns, 20 presets per pattern
- Indoor Ceiling Mount
- Optional Indoor Recessed Ceiling Mount
- Aluminum Construction
- Day / Night

Specifications

Image sensor: 1/4" Super HAD SONY CCD

Horizontal Resolution: 480 TV Lines (Color), 570 TV Lines (B/W night mode)

Pan Angle: 360° continuous pan rotation

Pan Speed: $0.1-180^{\circ}$ /s Tilt Speed: 15-60°/s Pixels: 768 x 494 SN Ratio: > 50db **Gain Control:** Auto/Manual **Back Light**

Compensation: 22X **Optical Zoom:**

10X Digital Zoom: 4 ~ 86mm, F1.6 Lens:

Preset Positions: 127

Comm Port: RS485 Pelco-D, Pelco-P selectable

Auto/Manual

Operating $0C \sim 50C (22F \sim 122F)$ Temperature

Power Supply: 12VDC (included)